

BUILDINGENERGY BOSTON

Monitoring Energy Performance & IAQ: Multifamily Energy Star vs. PHIUS+

August 13, 2020 · 1:00pm

Presenters:

Katrin Klingenberg (PHIUS), Connor Jansen
(Slipstream), & Lisa White (PHIUS)



www.phius.org

PHIUS+ CERTIFICATION
- PASSIVE/ZERO
ENERGY READY
MULTIFAMILY
BUILDINGS

AGENDA

- PHIUS Mission & Vision
- Background on Verification and Certification
- Affordable Housing Trend
- PHIUS+ Case Studies



EXECUTIVE
DIRECTOR & CO-
FOUNDER:
KATRIN
KLINGENBERG,
M. ARCH, DIPL. ING.,
RA (GERMANY),
CPHC®

The PHIUS mission

is to address the climate crisis through passive/zero energy ready buildings that can both mitigate and adapt to climate change. As a society overall we must get to 100% renewable energy. PHIUS+ is a design strategy that focuses on conservation first. It represents the best way to cost optimize buildings on the path to zero.

The PHIUS vision

is “to make high-performance passive building commonplace”.

PROGRAMS, PRODUCTS & SERVICES

PHIUS develops and promotes Passive/Zero Energy Ready & Source Zero Building Standards, practices, and certifications for buildings, professionals and products:

Project Certification Programs:

- PHIUS[®]+ certified passive/zero energy ready
- PHIUS+ source zero certified

Product Certification Programs:

- Windows
- Wall assemblies
- Ventilation systems

Professional Certificate Programs:

- Certified passive house consultant (CPHC[®])
- Certified builder (PHIUS Certified Builder)
- Certified onsite verifier (PHIUS+ Certified Rater/Verifier)

Research & Development Program:

- Materials/systems verification standards development
- Monitoring – proof of concept
- Details and mechanical systems catalogue

Products:

- WUFI Passive (Sales agent for NA)
- Conference proceedings
- E-books and other publications



Calculation based on ISO 10077-2, EN 673, EN 410

Product name: **ALPEN 725 High Performance Casement** Center-of-glass properties

ASHRAE/IECC /DOE North American Climate Zone	North, East, West-facing	PHIUS Passive House Institute US	Alpen HPP 725-7H No Grids		
	South-facing				
Whole-window installed U-value		Ucog-Value			
Climate specific recommendations:		SHGC	W/m2K	BTU/hr.ft2.F	
8	1.02 0.18	0.558	0.703	0.124	
7	1.00 0.18	0.558	0.678	0.119	
6	1.00 0.18	0.558	0.684	0.120	
5	1.00 0.18	0.558	0.686	0.121	
4	1.01 0.18	0.558	0.692	0.122	
Marine North	1.01 0.18	0.558	0.695	0.122	
Marine South	1.02 0.18	0.558	0.702	0.124	
3	1.01 0.18	0.558	0.698	0.123	
2 West	1.03 0.18	0.558	0.716	0.126	
2 East	1.03 0.18	0.558	0.716	0.126	

ALPEN 725 High Performance Allmetal 250P SST	FRAME				Psi-spacer		Psi-opaque
	Frame height	U-frame		ψ		W/mK	
	mm	in	W/m2K	BTU/hr.ft2.F	W/mK		
Head	73	2.86	1.15	0.20	0.054	0.031	0.143
Sill	73	2.86	1.16	0.20	0.054	0.031	BTU/hr.ft.F
left jamb	73	2.86	1.16	0.20	0.054	0.031	0.083
right jamb	73	2.86	1.16	0.20	0.054	0.031	Grade B

Valid through October 2018












WHAT DOES PHIUS DO?



PHIUS MILESTONES:


- 2003** Katrin Klingenberg built the first passive house in North America
- 2006** The 1st North American Passive House Conference was held in MN
- 2007** PHIUS was founded, became a non profit in 2009
- 2008** PHIUS created the design professional credential, CPHC[®]
- 2011** PHIUS partnered with RESNET to create a brand new third-party QA/QC project certification, customized for passive & zero energy.
- 2012** PHIUS integrated Department of Energy's Zero Energy Ready Home requirements and EPA indoor airPLUS and launched the PHIUS+ Building certification program.
- 2015** PHIUS released the PHIUS+ 2015 building standard, the first climate-specific passive building standard in the world. PHIUS+ was developed in partnership with Building Science Corporation under a U.S. Department of Energy Grant
- 2018** PHIUS released PHIUS+ 2018 building standard updates on the path to ZERO

DOE HIGH PERFORMANCE STAIRCASE

							Source Zero Renewable Energy System
							Balanced Ventilation HRV/ERV
							Balanced Ventilation HRV/ERV
					SOLAR READY Depends on climate		SOLAR READY ALWAYS
							SOLAR READY ALWAYS
					Eff. Comps. & H ₂ O Distrib		Eff. Comps. & H ₂ O Distrib
							Eff. Comps. & H ₂ O Distrib
					 EPA Indoor airPLUS	 EPA Indoor airPLUS	 EPA Indoor airPLUS
							EPA Indoor airPLUS
					Ducts in Condit. Space		Ducts in Condit. Space
							Ducts in Condit. Space
			HVAC QI w/WHV	HVAC QI w/WHV	HVAC QI w/WHV		Micro-load HVAC QI
							Micro-load HVAC QI
			Water Management	Water Management	Water Management		Water Management
							Water Management
			Independent Verification	Independent Verification	Independent Verification		Independent Verification
							Independent Verification
IECC 2009 Enclosure	IECC 2012 Enclosure	IECC 2009 Enclosure	IECC 2012 Enclosure	IECC 2012/15 Encl./ES Win.			Ultra-Efficient Enclosure
							Ultra-Efficient Enclosure
HERS 85-90	HERS 70-80	HERS 65-75	HERS 55-65	HERS 48-55			HERS 35-45
							HERS < 0
 IECC 2009	 IECC 2012	 ENERGY STAR v3	ENERGY STAR v3.1	 ZERH	 PHIUS PHIUS+	 PHIUS+ SourceZero	



NET SOURCE ENERGY




NET SOURCE ENERGY GOALS

PHIUS+ Core: Targeting the sweet spot for on-site conservation

PHIUS+ 2018: Reduced target, on the “fair share” glide-path to zero by 2030.

PHIUS+ Source Zero: Targeting annual net zero operational energy




PASSIVE BUILDING PRINCIPLES

Thermal Control




CONTINUOUS
INSULATION

Radiation Control



OPTIMIZED
WINDOWS
& SOLAR
GAINS

Air Control



AIR-TIGHT
CONSTRUCTION




BALANCED
VENTILATION
WITH HEAT
RECOVERY



Systems



EFFICIENT
APPLIANCES/
MINIMIZED
MECHANICAL
SYSTEMS

BUILDING SCIENCE PRINCIPLES






NEAR TERM/FUTURE GOALS:

- MAKE PHIUS+ AVAILABLE IN A CODE ADOPTABLE FORMAT
- CONTINUE TO DEVELOP/IMPROVE AFFORDABLE, EASY TO USE DESIGN, VERIFICATION, QUALITY ASSURANCE TOOLS AND PROTOCOLS FOR NET-ZERO, RESILIENT, GRID-FRIENDLY BUILDINGS FOR MOST ACCURATE RESULTS (+/-5%)
- DEVELOP MONITORING BASED COMMISSIONING PROTOCOLS
- MASS ADOPTION IN THE BUILDING SECTOR (RES, COMM, RETROFIT)

93% Modeled vs Actual Performance Data



670 PROJECTS IN NORTH AMERICA

7,000 UNITS
7,600,000 SQ FT



SITE EUIs OF 10-25 kBTU/ft².yr

~20-50% better than DOE's Zero Energy Home Program

PHIUS+ PROJECT CERTIFICATION

By the numbers

PHIUS+ Certified & Pre-Certified Square Footage



±C



PHIUS+ SOURCE ZERO



PHIUS+ SOURCE ZERO

19 CERTIFIED

18 PRE-CERTIFIED

23 SUBMITTED

60 TOTAL



Affordable Housing Successes


Low Income Housing Tax Credit (LITHC) Applications:

Housing agencies are awarding additional points in the LITHC application for affordable housing projects built to passive building standards.

Affordable Housing Successes (PHFA)

2015


+ 2.5% on PH



Affordable Housing Successes (PHFA)

2016


- 2%!



Affordable Housing Successes (PHFA)

2018


- 2%!



<https://passivehouseaccelerator.com/articles/2019-new-gravity-housing-conference-july-1st-2nd>


DATA SOURCE: PENNSYLVANIA HOUSING FINANCE AGENCY: MULTI-STORY AND SINGLE FAMILY TOWNHOUSE NEW CONSTRUCTION ONLY

© Passive House Institute US



39 State Housing Finance Agencies
Engaged to replicate PHFA strategy

15 COMMITTED!!



- [Pennsylvania Housing Finance Authority \(PHFA\)](#)
- [Connecticut Housing Finance Authority \(CHFA\)](#)
- [New Hampshire Housing Finance Authority \(NHHFA\)](#)
- [California Tax Credit Allocation Committee \(CTCAC\)](#)
- [Ohio Housing Finance Agency \(OHFA\)](#)
- [Illinois Housing Development Authority \(IHDA\)](#)
- [Virginia Housing Development Authority \(VHDA\)](#)
- [Idaho Housing and Finance Association \(IHFA\)](#)






Capital Flat 2, Philadelphia



ONION FLATS: THE BATTERY IN PHILADELPHIA

DISTILLERY NORTH

Icon ARCHITECTS



© Passive House Institute US

HOOK & LADDER

PHOTO: STARTRIBUNE.COM



© Passive House Institute US





ORCHARDS AT ORENCO PHASE II – PORTLAND, OR
58 units | 47,000 ft²

PARK AVENUE GREEN

South Bronx, NYC
154 Units
153,000 ft²



PAX FUTURA Seattle, WA

PHOTO: SLOAN RICHIE

45 UNITS



© Passive House Institute US



AFFORDABLE/MARKET RATE, 274 UNITS KANSAS CITY, MO





CHOM Village Center, Brewer, ME

47 UNITS – AFFORDABLE – BREWER, ME

© Passive House Institute US



425 GRAND
CONCOURSE,
BRONX, NY

289 UNITS
~300,000 SF

RESIDENTIAL
DAYCARE
OFFICES



TIERRA LINDA

LANDON BOONE BAKER ARCHITECTS

FIRST MULTI-
FAMILY IN THE
CITY OF
CHICAGO



© Passive House Institute US

Project Overview

Two new, 6-unit properties developed by LUCHA

Designed by Landon Bone Baker Architects

Built by Linn-Mathes and verified by Eco Achievers

Both part of ComEd Affordable Housing New Construction Program

Same layout, same orientation, same location in Chicago, IL

Constructed to two different energy efficiency standards

ENERGY STAR Homes Certification v3.1

Passive House Institute US (PHIUS+ 2015)

ComEd Funded Study - How do they compare?

Energy performance

Construction and operating costs



Indoor air quality (IAQ)



Photos Courtesy of LUCHA



Intensively monitored for energy and IAQ



Site Location and Floor Plan

ENERGY STAR



PHIUS+



Six-flat floorplan




Comparison of key property features

Feature	ENERGY STAR property	PHIUS+ property
Measured air leakage	1.90 (ACH50)	0.49 (ACH50)
Ceiling insulation	R-50	R-60
Wall insulation	R-14.5 assembly	R-29.4 assembly (EIFS)
Windows	Double-pane (U-value 0.29)	Triple-pane (U-value 0.17)
Heating	Two-stage gas furnace (AFUE 96)	Variable-speed ducted heat pump (HSPF 9.5, SEER 17.6)
Cooling	SEER 16 central A/C	
Ventilation	Continuous bath exhaust (40 CFM, 110 CFM boost)	Energy recovery ventilator (90-110 cfm)
Domestic hot water	Power-vented, 40-gal. gas water heater	
Cooking	Gas range w/ vented exhaust	Gas range w/ unvented exhaust (but ERV exhaust pickup in kitchen)
Laundry	Vented dryer w/ booster fan	Unvented compact dryer
Construction cost	\$178/ft ²	\$214/ft ²



The seasonal heating requirement for the PHIUS+ property appears to be about half that of ENERGY STAR property


- At the building level, the PHIUS+ property needs to be supplied with 42% as much heat seasonally as the ENERGY STAR property.
- The analysis is based on daily measured heat output for all heating systems in each building as a function of daily indoor-outdoor temperature difference. The relationship at the building level is reasonably linear for both properties.
- Cooling load analysis is still in development but appears to be about 14% less in the PHIUS+ property



The majority of the heating savings comes from air sealing and ERVs

- The ERV and air leakage reduction are synergistic measures.
- Windows did show a significant improvement in performance compared to the wall insulation improvement.
- The roof and foundation insulation proved to have the least heating load impact
- A similar study on cooling load savings is in progress


Component contributions to heating load savings



Comparing Air Leakage

- PHIUS property is far below the average air leakage
- 4 times lower than the Energy Star property
- Larger sample of low-rise multifamily properties that were tested for air leakage as part of a recent DOE code compliance study.



U.S. DOE Low-rise Multi-family Air Sealing Comparison



ERV Freeze Up


- During the 2019 Polar Vortex the ERV froze up for two days
- No electric back up heater was specified, retrofit opportunity in progress
- Caused a dip of indoor temperatures below 60F
- Several units were unoccupied at the time
- Interesting that Energy Star indoor air temperatures set above 80F

Polar Vortex Performance of ERV



Heat pumps under performing

- These are cold climate heat pumps rated at HSPF of 9.5 (COP 3.7@47f) that are operating at a combined seasonal COP of 1.69
- Based on the other testing we'd expect seasonal COPs closer 2.0-2.5
- Cooling performance was better yet still did not meet expectations



36% energy savings

- PHIUS property had a 36% reduction in overall energy usage compared to Energy Star
- The Energy Star property has an EUI of 52.5 kBtu/ft²-yr compared to the PHIUS property with an EUI of 33.7. (Was normalized energy usage from lights, water heating, and appliances)
- Clothes drier was a significant energy user as well as the lighting and miscellaneous


Annual Energy Use (Per Unit)	ENERGY STAR	PHIUS+
Natural gas (therms)		
Space heating ^a	347	--
Gas clothes dryer ^b	44	--
Gas water heater ^c	249	
Gas range/oven ^d	30	
Total	670	279
Electricity (kWh)		
Space heating ^a	324	2,219
Space cooling ^a	1,196	821
Space-conditioning standby ^a	60	331
Mechanical ventilation ^e	55	361
Clothes dryer ^b	142	933
Gas water heater (power-vented) ^c	109	
Gas range/oven + range hood ^d	46	
Lighting & other ^f	2,339	
Total	4,271	7,159
Total (kBtu)		
Natural Gas + Electricity (kBtu/ft ²)	52.5	33.7
Difference	-18.8	
% Difference	-36%	



Actual vs Predicted


- The normalized energy results across the 6 PHIUS units showed an EUI of 33.7 compared to the WUFI design model of 23.1
- The main differences were across heating, miscellaneous loads and appliances
- We also developed an ASHRAE 90.1 Appendix G energy model which had an EUI of 24.6

Comparing EUI to Predicted



Energy costs were lower for reasons you wouldn't expect

- Energy costs were only 18% less between normalized units while Energy savings in kBtu's was double that at 36%
- Energy cost savings come mostly from the difference in gas fuel prices between buildings
- These savings values would be highly dependent on what utilities served the homes



	ENERGY STAR	PHIUS+
Monthly service charge		
Natural gas	\$44.67	\$22.62
Electricity	\$17.02	\$18.82
Energy charge		
Natural gas (per therm)	66.0¢	61.1¢
Electricity (per kWh)	Summer ^a	11.9¢
	Non-summer	12.4¢
	Blended avg.	12.2¢
	10.4¢	10.2¢



Cutting the gas connection pays off

- Energy costs savings can increase from 18% over Energy Star with gas heat to upwards of 30% without gas demand charges
- Important to utilize heat pump water heaters as electric resistance would increase overall utility costs
- Significant emissions savings can also be found in switching to heatpump water heaters nearly doubling the CO2 reduction

All-Electric Utility Cost Comparison

Scenario	Air-source heat pump	Water heater	Range/oven	Total energy cost ^a	
				\$/unit/yr	Relative to ENERGY STAR property
Actual	Current	Gas	Gas	\$1,401	-18%
1	Current	Conventional Electric	Conventional Electric	\$1,491	-12%
2	Current	Heat pump ^b	Induction	\$1,248	-27%
3	High-efficiency ^c	Heat pump ^b	Induction	\$1,179	-31%

All-Electric Carbon Emission Comparison

Scenario (see Table 10)	Annual CO ₂ e emissions ^a (metric tons per unit per year)			
	Using <u>average</u> emissions factor for electricity ^b		Using <u>marginal</u> emissions factor for electricity ^c	
	MT/unit/yr	Relative to ENERGY STAR ^d	MT/unit/yr	Relative to ENERGY STAR ^d
Actual	5.75	-33%	6.90	-26%
1	4.95	-43%	6.93	-26%
2	3.99	-54%	5.59	-40%
3	2.69	-69%	3.77	-60%



Adaptation of the RESET standard for Tierra Linda

- Based on how tight the PHIUS building was constructed and the limited research on how natural air leakage contributes to providing adequate ventilation looked to RESET to test acceptability
- RESET is a monitoring-based standard for commercial spaces and provides useful benchmarks for residential
- RESET calls for no more than 10% “fail” days relative to these thresholds


PM2.5 Particulate Matter	TVOC Total Volatile Organic Compounds	CO2 Carbon Dioxide
Acceptable < 35 µg/m ³	Acceptable < 500 µg/m ³	Acceptable < 1,000 ppm
High Performance < 12 µg/m ³	High Performance < 400 µg/m ³	High Performance < 600 ppm



Unit occupants have a large effect on IAQ parameters


- As the example at right shows, unit occupancy has a large impact on the daily range of IAQ parameters such as particulates (PM2.5) and total volatile organic compounds (TVOCs). This indicates that these pollutants are mainly occupant-generated and not inherently sourced in the building itself.

Single Unit Before and After Move In



Most units pass the Acceptable threshold for CO2 and PM2.5 but none meet TVOC requirements


- No statistical difference in indoor air quality between the two properties
- The PHIUS+ property gets about 50% more air exchange than the Energy Star property on annual average
- Relative humidity levels across winter months were significantly better in the PHIUS property ranging between 30%-40% than the Energy Star property consistently below 30%.
- Summer humidity was well controlled in both properties between 50%-60%



The importance of continuous exhaust

- Average unit ventilation rate for the Energy Star property was approximately 60CFM
- Boosted operation of the fans to 110 CFM was controlled by light switch
- One unit consistently had bathroom lights on
- Other instances ranged between 10%-33% of hours
- If exhaust was only controlled by light switch operation ventilation would be drastically reduced


Energy Star Bathroom Fan Usage




Oven usage can cause lasting CO2 and PM2.5 spikes

- Over 800 oven use events were recorded
- Energy Star property has a manual range hood used about 40% of days
- PHIUS has an exhaust pickup within 8' of the oven as part of the ERV
- Combustion of natural gas by the oven itself produces a large plume of CO2 and PM2.5
- The decay of this plume over time following the oven event provides a useful metric sometimes taking over 4 hours to balance below baseline levels

Oven Usage CO2 and PM2.5



PHIUS+ CERTIFICATION



IMPORTANCE OF MONITORING



- PHIUS+ Certification is based on design, need to verify actual performance
- Quantify real energy/\$\$ savings
 - Shape incentives from local jurisdictions & rating systems
- Troubleshoot issues
- Adjust energy modeling protocol to improve predicted values

WHO'S RESPONSIBLE?

- This role is critical and often overlooked.
- **Someone** must be held accountable for verifying the performance of the building and rectifying any issues
- Design-Build firms have been more successful in the past due to responsibility carried by the same party throughout the process.



PHIUS Monitoring Protocol

FULL REPORT: <https://www.phius.org/Tools-Resources/PDF/PHIUS%20Monitoring%20Protocol%20v0.3.pdf>



GETTING STARTED: *WHAT'S THE QUESTION?*

1. Does actual energy use match predicted/modeled energy use?
 - If not, why?
 - How steady is the daily electrical load profile?
 - What kind of dashboard would motivate the occupants to save energy?
2. Is thermal comfort being delivered?
3. Is there satisfactory indoor air quality (IAQ)?
4. Is a mechanical system performing as expected?
5. Is an “edgy” moisture design for an assembly staying dry enough?

SELECT EQUIPMENT: *TO ANSWER THE QUESTION*

For Electric, Water, Gas, and Indoor Environment:

PHIUS recommends the Powerwise / Sitesage system

Equipment:

- CTs (current transducers) to measure electricity
- Non-invasive load monitoring (NILM) technologies not as accurate as knowing what you monitor from CT clamps
- Use thermostats that integrate with the monitoring system.
- Wired sensors = more reliable than wireless.

Installation Best Practices:

- Indoor space sensors should be placed 3-6' above the floor, in a representative thermal zone (not near ceiling).
- Wiring should be done in a place where it can be accessed later for troubleshooting the installation.
- Sensors and meters have an ID #, make sure this is noted during installation.

SELECT EQUIPMENT: *TO ANSWER THE QUESTION*

For Air Quality:

PHIUS recommends the RESET System

- Especially if PM2.5 is a concern.
- RESET is a full air quality standard, setting thresholds/targets/ideal ranges
- RESET provides accreditation for air monitors:
<https://www.reset.build/monitors>



PHIUS MONITORING 'TIERS'

Tiers	0	1	2	3	4	5
Report monthly utility bills, or allow PHIUS access, or Energy Star Portfolio	x	x	x	x	x	x
Monitor electrical mains + plugs		x	x	x	x	-
Monitor indoor temperature			x	x	x	-
Monitor lighting				x	x	-
Monitor major systems (heating, cooling, hot water, ventilation)				x	x	-
Monitor thermostat settings			x	x	x	-
Monitor major appliances, renewables					x	-
Monitor air quality (CO2, VOC, PM2.5, Radon)					x	-
Monitor relative humidity & operative temperatures					x	-
Special situations: moisture in assemblies, site weather, complex mechanicals, etc.						x
Estimated Cost	\$0	~\$500	~\$1000	~ \$2000	> \$2000	Varies

MONITOR YOUR PROJECT

FREE platforms

1. Energy Star Portfolio Manager
 - Input utility data each month
 - Benchmark against other similar types



2. WegoHome with Wegowise
 - Track, visualize and analyze utility usage
 - Benchmark your home against similar buildings
 - Measure building upgrade results
 - Identify spikes in energy and water usage
 - Online login – share with PHIUS

3. Green Button Alliance
 - Provides online access to utility bills for 3rd party organizations (PHIUS)
 - PHIUS is affiliate of program
 - Owner selects PHIUS as acceptable viewer of data



4. Share utility bills w/PHIUS. Get in touch with certification@phi.us to get set up on an automated system.

MONITOR YOUR PROJECT

1. PHIUS+ Project Monitoring Project w/PowerWise

- 10% discount when PHIUS project
- 'Basic' pre-packaged option already designed

2. PHIUS IAC (Industry Advisory Council) Monitoring Project w/PowerWise

- Potential funding available for equipment
- Client pays for design, installation, and maintenance
- 6 projects assigned, funding available for 30 over time
- Contact mknezo@phius.org


3. WegoData (\$1.50/month)

- Same as WegoHome, but automated



POTENTIAL FACTORS AFFECTING DIFFERENCES BETWEEN MODELED AND MONITORED

- Varying heating setpoint above/below 68°F
- Varying cooling setpoint above/below 77 ° F
- Climatic differences between measured year and ‘typical year’ used for modeling
- Varying number of occupants from modeled assumption (BR+1)
- Occupant behavior (work from home, kids vs adults, lifestyle, habits)
- Equipment tested *efficiency* varying from real performance
- System malfunction



STELLAR APARTMENTS

Eugene, OR


6 units


5,488 ft²



- 8 Meters per unit
- No common spaces
- Electric Heating
- No Cooling
- Heat Pump Water Heaters in outdoor mech closet

Individual Apartment Energy Use vs Average Energy Use







BEACH GREEN DUNES – CASE STUDY

FAR ROCKAWAY, QUEENS

Total energy use in Btu per square foot


Wegowise Portal

Name	Full-Year Sum	
43-06 63rd St	91.8k*	✓
Flushing Steam Buildin...	85.8k*	✓
140-74 34th Avenue	84.8k*	✓
138-49 Barclay Avenue	77.6k*	✓
95-11 64th Rd	75k	✓
28 Gilcrest Rd	74.2k*	✓
141-28 84th Drive	73.7k*	✓
Austin St	70.5k*	✓
113th St	69.1k*	✓
99-22 67th Rd	63k*	✓
Kew Gardens	61.7k*	✓
140-26 Franklin Avenue	60.5k*	✓
9 Chelsea Place	50.9k*	✓
193-04 Horace Harding	48.9k*	✓
90-11 160th St	41.7k	✓
65-54 Austin St	32.7k	✓
BGN	22.6k*	✓

Detailed data per month

You are currently viewing the last 2 years of data only

Zoom out




BEACH GREEN DUNES

Name	Full-Year Sum	
140-74 34th Avenue	84.8k*	
138-49 Barclay Avenue	77.6k*	
95-11 64th Rd	75k	
28 Gilcrest Rd	74.2k*	
141-28 84th Drive	73.7k*	
Austin St	70.5k*	
113th St	69.1k*	
99-22 67th Rd	63k*	
Kew Gardens	61.7k*	
140-26 Franklin Avenue	60.5k*	
9 Chelsea Place	50.9k*	
193-04 Horace Harding	48.9k*	
90-11 160th St	41.7k	✓
65-54 Austin St	32.7k	
BGN	22.6k*	✓

Detailed data per month

You are currently viewing the last 2 years of data only

Zoom out




Differences
Ventilation & Airtightness

LOUGHRAN RESIDENCE

93% Modeled vs Actual



1248 - Electric Consumption (kWh)



WUFI-Passive used as modeling tool

Modeled Measured Net Measured w/ PV


© Passive House Institute US

Type: Single family
Occupants: 4
Location: Illinois
CPHC: Ryan Abendroth




LOUGHRAN RESIDENCE


Sitesage Portal



LOUGHRAN RESIDENCE

March 2019 - March 2020





LESSONS LEARNED *from PHIUS+ project teams*

- Assigning roles/responsibilities upfront is critical.
Need a point of contact for design, installation, monitoring, debugging, resident.
- Monitoring never seems to be a priority, just “nice to have”.
Hard to place priority on that over other budgetary/time constraints.
- Systems work incorrectly (or not at all) quite often. Meters also break.
Whose responsibility is it to check up on that, and then fix it?
- Monitoring should be part of the design process at the start, not finish.
And maintained throughout all phases of design.
- Critical to follow through with plan during construction.
And inspect/track after final installation.

THANKS!

